

ELECTRIC STRAPPING TOOL FOR POLYPROPYLENE AND POLYESTER STRAP WITH VIBRATION SEALING



TECHNICAL SPECIFICATIONS	
DIMENSIONS	
Length	315 mm • 12.4"
Width	140 mm • 5.5"
Height	183 mm • 7.2"
Weight	3.8 kgs • 8,4lb
FEEDING	
Battery	14.8V - 3 A/h LI-PO
PERFORMANCE	
Max. tension force	3500N
Tensioning speed	12mt/m
Sealing	friction weld seal
Joint strength	80% of plastic strap strength*

\* depends of strap quality

MODEL			
CODE	TYPE	STRAP	THICKNESS
T219997	ITA21 / 16-19 mm with one battery	PP-PET 16 mm	0.8 mm ÷ 1.05 mm
		PET 19 mm	0.7 mm ÷ 1.27 mm
T2199971	ITA21 / 16-19 mm with one battery and charger	PP-PET 16 mm	0.8 mm ÷ 1.05 mm
		PET 19 mm	0.7 mm ÷ 1.27 mm
T2199972	ITA21 / 16-19 mm with two batteries and charger	PP-PET 16 mm	0.8 mm ÷ 1.05 mm
		PET 19 mm	0.7 mm ÷ 1.27 mm


POLYESTER STRAP



POLYESTER STRAP



POLYPROPYLENE STRAP



ITATOOLS s.r.l.

Via Rossini, 340 - 21042 Caronno Pertusella (VA) - ITALY • p.iva 05022340961

Tel.: +39.02.96450619 - Fax +39.02.9659747 • E-mail: info@itatools.it - www.itatools.com